

Low Voltage ABC Cable

Overhead cable for aerial distribution and service connection

Low Voltage ABC Cable is prepared for preliminary product selection and quotation review. This product is used for overhead distribution routes where conductor arrangement, insulation, messenger or neutral support and installation environment determine cable selection.



VOLTAGE

0.6/1kV

CONDUCTOR

Aluminum / reinforced conductor route, according to overhead cable standard

TYPICAL USE

Aerial bundled cable systems

STANDARDS

IEC 60502-1

DATA SCOPE

2 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm voltage, conductor, core arrangement, messenger/neutral and installation span.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Aerial bundled cable systems
- overhead service drops
- rural and urban distribution networks
- utility line upgrade projects.

Selection logic

- Confirm voltage grade, conductor material, core arrangement, messenger/neutral requirement, installation span and applicable utility standard.

Construction Overview

Item	Website-ready content
Product route	Aluminum or copper conductor with insulation and optional messenger or bundled arrangement according to product type.
Voltage	0.6/1kV
Conductor	Aluminum / reinforced conductor route, according to overhead cable standard
Standards	IEC 60502-1
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
Duplex ABC (1 Phase + 1 Neutral) - Self Supporting	2 x 16 mm ² - 3 x 50 mm ²	See table	See table	135 - 525
Quadruplex ABC (3 Phases + 1 Neutral) - Self Supporting	4 x 16 mm ² - 4 x 150 mm ²	See table	See table	270 - 2040

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

Duplex ABC (1 Phase + 1 Neutral) - Self Supporting

Reference table for preliminary selection and quotation review.

Size & Configuration	Phase Cond. Dia. (mm)	Insulation Thickness (mm)	Approx. Bundle OD (mm)	Approx. Weight (kg/km)	Max DC Res. @20°C (Ω/km)
Duplex ABC (1 Phase + 1 Neutral) - Self Supporting					
2 x 16 mm ²	4.7	1.2	14.2	135	1.91
2 x 25 mm ²	5.9	1.2	16.6	195	1.20
2 x 35 mm ²	6.9	1.2	18.6	260	0.868
2 x 50 mm ²	8.1	1.5	22.2	350	0.641
Triplex ABC (2 Phases + 1 Neutral) - Self Supporting					
3 x 16 mm ²	4.7	1.2	15.3	200	1.91
3 x 25 mm ²	5.9	1.2	17.9	295	1.20
3 x 35 mm ²	6.9	1.2	20.1	390	0.868
3 x 50 mm ²	8.1	1.5	23.9	525	0.641

Quadruplex ABC (3 Phases + 1 Neutral) - Self Supporting

Reference table for preliminary selection and quotation review.

Size & riCpontfiigounration	Phase Cond. Dia. (mm)	Insulation Thickness (mm)	Approx. Bundle OD (mm)	Approx. Weight (kg/km)	Max DC Res. @20°C (Ω/km)
Quadruplex ABC (3 Phases + 1 Neutral) - Self Supporting					
4 x 16 mm ²	4.7	1.2	17.1	270	1.91
4 x 25 mm ²	5.9	1.2	20.0	390	1.20
4 x 35 mm ²	6.9	1.2	22.5	520	0.868
4 x 50 mm ²	8.1	1.5	26.8	700	0.641
4 x 70 mm ²	9.7	1.5	30.6	970	0.443
4 x 95 mm ²	11.4	1.7	35.7	1330	0.320
4 x 120 mm ²	12.9	1.7	39.3	1650	0.253
4 x 150 mm ²	14.4	1.9	43.9	2040	0.206