

XHHW-2 Wire

Building wire for electrical systems and service entrance wiring

XHHW-2 Wire is prepared for preliminary product selection and quotation review. This product is used for building electrical systems where conductor material, insulation rating, flame performance and local wiring rules determine product selection.



VOLTAGE

600V

CONDUCTOR

Copper conductor route, confirmed by technical table

TYPICAL USE

Residential and commercial wiring

STANDARDS

UL 44

DATA SCOPE

1 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm conductor, insulation type, voltage rating, size and local wiring rule.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Residential and commercial wiring
- panel feeders
- branch circuits
- service entrance wiring
- conduit, tray or building electrical installation routes.

Selection logic

- Confirm conductor material, voltage rating, insulation type, installation method and applicable UL, IEC or local wiring standard before selection.

Construction Overview

Item	Website-ready content
Product route	Copper or aluminum conductor with thermoplastic or cross-linked insulation according to the selected building wire type and standard.
Voltage	600V
Conductor	Copper conductor route, confirmed by technical table
Standards	UL 44
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
Stranded Copper XHHW-2 - 600V	14 AWG - 500 kcmil	See table	See table	19 - 1665

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

Stranded Copper XHHW-2 - 600V

Reference table for preliminary selection and quotation review.

Size (AWG / kcmil)	No. of Strands	Insulation Thick. (mils/mm)	Approx. OD (mils/mm)	Approx. Weight (lb/kft)	Allowable Ampacity @ 90°C (Amps)
Stranded Copper XHHW-2 - 600V					
14 AWG	7	30 / 0.76	131 / 3.33	19	15
12 AWG	7	30 / 0.76	150 / 3.81	27	20
10 AWG	7	30 / 0.76	174 / 4.42	40	30
8 AWG	7	45 / 1.14	233 / 5.92	67	55
6 AWG	7	45 / 1.14	271 / 6.88	101	75
4 AWG	7	45 / 1.14	317 / 8.05	153	95
2 AWG	7	45 / 1.14	379 / 9.63	233	130
1/0 AWG	19	55 / 1.40	475 / 12.07	375	170
2/0 AWG	19	55 / 1.40	520 / 13.21	466	195
4/0 AWG	19	55 / 1.40	632 / 16.05	724	260
500 kcmil	37	65 / 1.65	910 / 23.11	1665	430