

Armoured Control Cable

Control cable for signal, control and instrumentation circuits

Armoured Control Cable is prepared for preliminary product selection and quotation review. This product is used for control, monitoring and signal circuits where core number, conductor size, shielding, flame performance and installation environment affect cable selection.



VOLTAGE

450/750V, 0.6/1kV

CONDUCTOR

Steel or reinforced conductor route, according to standard

TYPICAL USE

Control panels

STANDARDS

GB/T 9330; IEC 60502-1; BS 5467

DATA SCOPE

2 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm cores, conductor size, screen/armour, sheath and installation route.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Control panels
- instrumentation circuits
- industrial automation
- substation control systems
- building services and process equipment control wiring.

Selection logic

- Confirm core number, conductor size, shielding or armour requirement, flame-retardant requirement and installation environment.
- Project standards should be reviewed before final cable confirmation.

Construction Overview

Item	Website-ready content
Product route	Multi-core copper conductor with insulation, optional screen or armour and outer sheath according to the selected cable type.
Voltage	450/750V, 0.6/1kV
Conductor	Steel or reinforced conductor route, according to standard
Standards	GB/T 9330; IEC 60502-1; BS 5467
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
450/750V STA Control Cable (Double Steel Tape Armour - KVV	4 x 1.5 - 61 x 1.5	4 x 1.5 - 61 x 1.5	11.6 - 32.5	230 - 1950
0.6/1kV SWA Control Cable (Galvanized Steel Wire Armour -	4 x 1.5 - 61 x 1.5	4 x 1.5 - 61 x 1.5	12.8 - 35.5	315 - 2150

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

450/750V STA Control Cable (Double Steel Tape Armour - KVV22)

Reference table for preliminary selection and quotation review.

No. of Cores x Cross Section (mm ²)	Nominal Conductor Dia. (mm)	Nominal Insulation Thick. (mm)	Steel Tape Thickness (mm)	Approx. Overall Dia. (mm)	Approx. Weight (kg/km)
450/750V STA Control Cable (Double Steel Tape Armour - KVV22)					
4 x 1.5	1.56	0.7	0.2	11.6	230
7 x 1.5	1.56	0.7	0.2	13.2	305
10 x 1.5	1.56	0.7	0.2	16.1	410
14 x 1.5	1.56	0.7	0.2	17.3	485
19 x 1.5	1.56	0.7	0.2	19.2	585
24 x 1.5	1.56	0.7	0.2	21.6	710
30 x 1.5	1.56	0.7	0.2	23.2	830
37 x 1.5	1.56	0.7	0.5	25.8	1260
44 x 1.5	1.56	0.7	0.5	28.5	1480
61 x 1.5	1.56	0.7	0.5	32.5	1950

0.6/1kV SWA Control Cable (Galvanized Steel Wire Armour - IEC/BS)

Reference table for preliminary selection and quotation review.

No. of Cores x Cross Section (mm ²)	Nominal Conductor Dia. (mm)	Nominal Insulation Thick. (mm)	Steel Wire Dia. (mm)	Approx. Overall Dia. (mm)	Approx. Weight (kg/km)
0.6/1kV SWA Control Cable (Galvanized Steel Wire Armour - IEC/BS)					
4 x 1.5	1.56	0.7	0.9	12.8	315
7 x 1.5	1.56	0.7	0.9	14.5	420
10 x 1.5	1.56	0.7	1.25	17.5	580
14 x 1.5	1.56	0.7	1.25	19.0	720
19 x 1.5	1.56	0.7	1.25	21.0	850
24 x 1.5	1.56	0.7	1.6	23.5	1120
30 x 1.5	1.56	0.7	1.6	25.5	1250
37 x 1.5	1.56	0.7	1.6	27.5	1350
44 x 1.5	1.56	0.7	1.6	30.5	1550
61 x 1.5	1.56	0.7	2.0	35.5	2150