


Concentric Flat Cable

Concentric cable for service entrance and utility distribution review

Concentric Flat Cable is prepared for preliminary product selection and quotation review. This product is used for low or medium voltage service connections and utility distribution where concentric neutral or earth construction is required. Cable structure, conductor material, insulation level and applicable standard should be reviewed according to the project route.



VOLTAGE

0.6/1kV

CONDUCTOR

Confirmed by product standard and project requirement

TYPICAL USE

Service entrance connections

STANDARDS

BS 7870-3.11

DATA SCOPE

1 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm voltage, conductor, neutral/earth arrangement, sheath and installation route.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Service entrance connections
- utility distribution networks
- overhead or underground service routes
- projects requiring concentric neutral or earth cable construction.

Selection logic

- Confirm voltage grade, conductor material, concentric neutral or earth arrangement, installation route and required standard.
- For utility projects, local grid practice and tender documents should be checked before final selection.

Construction Overview

Item	Website-ready content
Product route	Phase conductor with insulation and concentric neutral/earth wires or screen arrangement. Outer sheath and detailed structure depend on the project standard and product type.
Voltage	0.6/1kV
Conductor	Confirmed by product standard and project requirement
Standards	BS 7870-3.11
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
Pure Copper Flat Straight Concentric (BS 7870)	1 x 4.0 - 1 x 25	1.04mm x 5 - 1.70mm x 11	See table	135 - 485

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

Pure Copper Flat Straight Concentric (BS 7870)

Reference table for preliminary selection and quotation review.

Nom. Area (mm²)	Phase Dia. (mm)	Concentric Copper Wires	Approx Dimensions (mm)	Weight (kg/km)
Pure Copper Flat Straight Concentric (BS 7870)				
1 x 4.0	2.6	1.04mm x 5	6.2 x 8.8	135
1 x 6.0	3.1	1.04mm x 7	6.8 x 9.5	165
1 x 10	4.0	1.35mm x 7	7.8 x 10.8	225
1 x 16	5.1	1.35mm x 11	9.2 x 12.5	315
1 x 25	6.4	1.70mm x 11	11.0 x 14.8	485