

Flame Retardant Cable IEC 60332

Flame retardant cable for project fire-performance requirements

Flame Retardant Cable IEC 60332 is prepared for preliminary product selection and quotation review. This product is used where flame spread performance must be reviewed together with normal electrical parameters and installation conditions.



VOLTAGE

0.6/1kV, 35kV

CONDUCTOR

Copper conductor route, confirmed by technical table

TYPICAL USE

Industrial systems

STANDARDS

IEC 60332-1-2; IEC 60332-3-22

DATA SCOPE

1 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm special performance, voltage, conductor, standard and installation condition.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Industrial systems
- building electrical routes
- public infrastructure
- control and power circuits requiring flame-retardant cable selection.

Selection logic

- Confirm flame-retardant standard, voltage, conductor size, insulation/sheath material and installation route before quotation.

Construction Overview

Item	Website-ready content
Product route	Conductor with insulation and flame-retardant sheath or compound according to the selected product standard.
Voltage	0.6/1kV, 35kV
Conductor	Copper conductor route, confirmed by technical table
Standards	IEC 60332-1-2; IEC 60332-3-22
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
Flame Retardant Cable IEC 60332 - Technical Table 1	3 x 1.5 - 3 x 50	See table	See table	12.1 - 0.387

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

Flame Retardant Cable IEC 60332 - Technical Table 1

Reference table for preliminary selection and quotation review.

Nom. Area (mm²)	Approx. OD (mm)	Approx. Weight (kg/km)	Current Rating @ 30°C (A)	Max. Resistance (Ω/km)
3 x 1.5	10.5	155	23	12.1
3 x 2.5	11.2	195	32	7.41
3 x 4.0	12.5	260	42	4.61
3 x 6.0	13.8	330	54	3.08
3 x 10	16.2	510	75	1.83
3 x 16	18.5	720	100	1.15
3 x 25	22.5	1120	135	0.727
3 x 35	25.2	1450	165	0.524
3 x 50	28.5	1950	205	0.387