

H1Z2Z2-K Solar Cable EN 50618

Solar cable for PV and renewable energy project supply

H1Z2Z2-K Solar Cable EN 50618 is prepared for preliminary product selection and quotation review. This product is used in photovoltaic power systems where UV resistance, temperature rating, voltage grade and outdoor durability are important for project selection.



VOLTAGE

1.0kV, 1.5kV

CONDUCTOR

Tinned copper conductor route, confirmed by technical table

TYPICAL USE

PV module interconnection

STANDARDS

EN 50618; IEC 60228

DATA SCOPE

1 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm voltage, conductor size, UV rating, temperature class and standard.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- PV module interconnection
- solar power plants
- rooftop solar systems
- BESS and renewable energy DC cable routes.

Selection logic

- Confirm rated voltage, conductor size, insulation/sheath material, UV and temperature requirements, flame performance and applicable project standard.

Construction Overview

Item	Website-ready content
Product route	Tinned copper or copper conductor with solar-grade insulation and sheath according to the selected PV cable standard.
Voltage	1.0kV, 1.5kV
Conductor	Tinned copper conductor route, confirmed by technical table
Standards	EN 50618; IEC 60228
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
H1Z2Z2-K Tinned Copper Solar Cable - 1500V DC	2.5 - 35.0	See table	See table	8.21 - 0.56

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

H1Z2Z2-K Tinned Copper Solar Cable - 1500V DC

Reference table for preliminary selection and quotation review.

Sectional Area (mm²)	Cond. Construction (n/mm)	Nom. Outer Dia. (mm)	Approx. Weight (kg/km)	Current Rating @ 60°C (Amps)	Max. DC Resistance @ 20°C (Ω/km)
H1Z2Z2-K Tinned Copper Solar Cable - 1500V DC					
2.5	50 / 0.25	5.0	45	41	8.21
4.0	56 / 0.30	5.6	65	55	5.09
6.0	84 / 0.30	6.2	85	70	3.39
10.0	80 / 0.40	7.6	135	98	1.95
16.0	126 / 0.40	9.0	205	132	1.24
25.0	196 / 0.40	11.2	310	176	0.79
35.0	276 / 0.40	13.0	415	218	0.56