

MV Aerial Bundled Cable (ABC) - 19/33(36) kV IEC 60502-2

Overhead cable for aerial distribution and service connection

MV Aerial Bundled Cable (ABC) - 19/33(36) kV IEC 60502-2 is prepared for preliminary product selection and quotation review. This product is used for overhead distribution routes where conductor arrangement, insulation, messenger or neutral support and installation environment determine cable selection.



VOLTAGE

19/33kV, 36kV

CONDUCTOR

Aluminum / reinforced conductor route, according to overhead cable standard

TYPICAL USE

Aerial bundled cable systems

STANDARDS

IEC 60502-2

DATA SCOPE

2 technical table(s) included for preliminary selection

SELECTION NOTE

Confirm voltage, conductor, core arrangement, messenger/neutral and installation span.

For quotation review, provide cable type, standard, size, quantity and project destination.

ethan@farwalkcable.com | +86 155 5800 6344

Application & Selection Summary

Typical applications

- Aerial bundled cable systems
- overhead service drops
- rural and urban distribution networks
- utility line upgrade projects.

Selection logic

- Confirm voltage grade, conductor material, core arrangement, messenger/neutral requirement, installation span and applicable utility standard.

Construction Overview

Item	Website-ready content
Product route	Aluminum or copper conductor with insulation and optional messenger or bundled arrangement according to product type.
Voltage	19/33kV, 36kV
Conductor	Aluminum / reinforced conductor route, according to overhead cable standard
Standards	IEC 60502-2
Confirmation	Final structure, dimensions and packing should follow selected standard, quotation review and order specification.

Readable Data Index

Data route	Size / rating range	Construction	Diameter / OD	Resistance / weight / rating
IEC 60502-2 33kV MV ABC (3 Phases + Bare GSW Messenger)	3 x 50 mm ² + 50 mm ² - 3 x 240 mm ² + 95 mm ²	34.5 - 46.2	See table	3200 - 6700
IEC 60502-2 33kV MV ABC (3 Phases + Bare AAAC Messenger)	3 x 50 mm ² + 50 mm ² - 3 x 240 mm ² + 95 mm ²	34.5 - 46.2	See table	2900 - 6100

Data boundary: these tables support website launch, quotation review and preliminary product selection. For project execution, final dimensions, electrical performance, packing and compliance documents should be confirmed against the selected project standard and order specification.

IEC 60502-2 33kV MV ABC (3 Phases + Bare GSW Messenger)

Reference table for preliminary selection and quotation review.

Size (Phase + Messenger)	Insulation Thickness (mm)	Phase Core Dia. (mm)	Approx. Bundle OD (mm)	Approx. Weight (kg/km)
IEC 60502-2 33kV MV ABC (3 Phases + Bare GSW Messenger)				
3 x 50 mm ² + 50 mm ²	8.0	34.5	74.0	3200
3 x 70 mm ² + 50 mm ²	8.0	36.2	78.0	3600
3 x 95 mm ² + 50 mm ²	8.0	38.0	82.0	4000
3 x 120 mm ² + 70 mm ²	8.0	39.5	86.5	4700
3 x 150 mm ² + 70 mm ²	8.0	41.5	90.5	5100
3 x 185 mm ² + 95 mm ²	8.0	43.5	96.0	5900
3 x 240 mm ² + 95 mm ²	8.0	46.2	102.0	6700

IEC 60502-2 33kV MV ABC (3 Phases + Bare AAAC Messenger)

Reference table for preliminary selection and quotation review.

Size (Phase + Messenger)	Insulation Thickness (mm)	Phase Core Dia. (mm)	Approx. Bundle OD (mm)	Approx. Weight (kg/km)
IEC 60502-2 33kV MV ABC (3 Phases + Bare AAAC Messenger)				
3 x 50 mm ² + 50 mm ²	8.0	34.5	74.0	2900
3 x 70 mm ² + 50 mm ²	8.0	36.2	78.0	3300
3 x 95 mm ² + 50 mm ²	8.0	38.0	82.0	3700
3 x 120 mm ² + 70 mm ²	8.0	39.5	86.5	4200
3 x 150 mm ² + 70 mm ²	8.0	41.5	90.5	4600
3 x 185 mm ² + 95 mm ²	8.0	43.5	96.0	5300
3 x 240 mm ² + 95 mm ²	8.0	46.2	102.0	6100